

Versa® Pro 50



Improve the BYOD experience in huddle spaces and small conference rooms by adding professional quality audio and video.

Professional, crystal-clear audio

Includes ClearOne's CONVERGE® Huddle DSP mixer and Ceiling Mic Array for crystal-clear voice clarity and an unrivaled audio experience.

- > One CONVERGE® Huddle audio DSP mixer for a professional audio experience
- > One Ceiling Microphone Array with 360-degree coverage reducing noise and reverberation.
- > Clutter-free with optional CONVERGE Huddle VESA mount
- > One UNITE® 50 ultra-wide 120-degree ePTZ camera with 1080p30, and 3x digital zoom to capture all participants in a huddle space or small room.
- > Complimentary 90-day trial of COLLABORATE Space, our powerful collaboration application with a full suite of audio, video, and meeting tools in a persistent space.



APPLICATIONS

- BYOD video conferencing
- BYOD audio conferencing
- In-Room presentation

WORKSPACES

- Huddle spaces
- Small meeting rooms
- Executive offices

Enhances Any Cloud-based App

Add pro-quality audio and HD video to your app, such as COLLABORATE Space, Skype® for Business, Zoom, WebEx, and GoToMeeting.

Great ideas need to be seen - and heard!™

Versa® Pro 50

INCLUDES

- CONVERGE® Huddle
- UNITE® 50 USB ePTZ HD camera
- Ceiling Mic Array (White)

CONVERGE HUDDLE

INPUTS

- 3 channel balanced audio mic/line inputs with AEC
- 1 channel balanced audio line input without AEC
- 3.81mm orange-color Phoenix/Euroblock type male header, push-on mini-terminal block

LINE OUTPUTS

- 2 channel balanced audio line outputs, 3.81mm black-color Phoenix/Euroblock type male header, push-on mini-terminal block
- 1 USB 3.0 Type-B
- 2 USB 3.0 Type-A
- RJ-45, 10/100/1000Mbps, passthrough to USB-B 3.0

HDMI RESOLUTIONS

- 1600 x 1200p @ 60Hz, 4:3 ratio
- 1920 x 1200p @ 60Hz, 16:10 ratio
- 2560 x 1440p @ 60Hz, 16:9 ratio

UNITE 50 EPTZ HD CAMERA

- 120° wide-angle field view with EPTZ support
- Full auto-focus, limited-distortion lens
- Low-light 2D and 3D algorithm
- Image SNR as high as 55dB

CONTROL

- Remote control, USB (UVC), RS-232

CEILING MICROPHONE ARRAY

ACOUSTIC CHARACTERISTICS

- Polar Pattern: Cardioid
- Dynamic Range: 80 dB, 1 kHz @ max SPL
- Signal/Noise Ratio: 60 dBA, 1kHz @ 1Pa
- Frequency Response: 100 Hz - 12kHz
- Sensitivity: 114 mV/Pa

ELECTRICAL CHARACTERISTICS

- Element: Fixed-charge back plate permanently polarized condenser
- Phantom Power Requirement: 12-52 vdc, 2 mA typical
- Impedance: 200 Ω

PART NUMBER

- 930-3200-050

SALES AND INQUIRIES

Headquarters

5225 Wiley Post Way
Suite 500
Salt Lake City, UT 84116

US & Canada

Tel: 801.975.7200
Fax: 801.303.5711

International

Tel: +1.801.975.7200
global@clearone.com

Sales

Tel: 801.975.7200
sales@clearone.com

Tech Support

Tel: 801.974.3760
tech.support@clearone.com